

Housing - HC-D 7-AML-24/GR - 1773035


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



HEAVYCON panel mounting base D7, with single locking latch, height 24 mm, straight, zinc die-cast



Key Commercial Data

Packing unit	10 pc
GTIN	 4 017918 122324
Weight per Piece (excluding packing)	45.26 g
Custom tariff number	85389099
Country of origin	Germany

Technical data

Dimensions

Height	24 mm
Width	38 mm
Length	28 mm
Length of the assembly cutout	21.5 mm
Width of the assembly cutout	21.5 mm

Ambient conditions

Degree of protection of housing (IP)	IP54
	IP65 (with sealing screw)
Ambient temperature (operation)	-40 °C ... 125 °C

General

Note	For contact inserts HC-D7, D8, A3, A4, B5, HS2-D7
Type	D7
Housing type	Panel mounting base
Locking type	With single locking latch
Screw connection	none
Housing material	Zinc die-cast

Housing - HC-D 7-AML-24/GR - 1773035

Technical data

General

Housing surface material	Powder-coated, gray (metal housing)
Seal material	NBR
Material lock	Steel, galvanized and passivated

Classifications

eCl@ss

eCl@ss 4.0	27140816
eCl@ss 4.1	27140816
eCl@ss 5.0	27143424
eCl@ss 5.1	27143424
eCl@ss 6.0	27143424
eCl@ss 7.0	27440209
eCl@ss 8.0	27440202
eCl@ss 9.0	27440202

ETIM

ETIM 2.0	EC000437
ETIM 3.0	EC000437
ETIM 4.0	EC000437
ETIM 5.0	EC000437

UNSPSC

UNSPSC 6.01	31261502
UNSPSC 7.0901	31261502
UNSPSC 11	31261502
UNSPSC 12.01	31261502
UNSPSC 13.2	31261502

Approvals

Approvals

Approvals

EAC / GL

Ex Approvals

Approvals submitted

Housing - HC-D 7-AML-24/GR - 1773035

Approvals

Approval details

EAC

GL

Accessories

Accessories

Mounting material


Sealing screw - HC-D 7-DS-IP65 - 1686229



Sealing screw, for IP65 protection


Drawings

Dimensional drawing



Dimensional drawing

Dimensional drawing



Panel cutout